

R-CRETE INC.

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT IDENTITY

EMERGENCY ASSISTANCE

R-CRETE CAM STAIN WB-A3/STONE STAIN

Acrylic polymer in water
Dot Name: Acrylic polymer in water
Dot ID No.: Non regulated

R-CRETE INC.
P.O. Box 80286
Rancho Santa Margarita, CA 92688
949-888-8401 Fax 949-858-5720

SECTION 2 - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS REG. NO.</u>	<u>AMT(%)</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Ammonia	7664-41-7	~.02 %/wt.	50 ppm	25 ppm
Acrylate esters	Mixture	~.05 %/wt.	Unknown	10 ppm-TWA
Benzol Alcohol	100-57-6	~ 1%/wt.		

This MSDS complies with the OSHA Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not 'Hazardous' per this OSHA Standard and are considered to be trade secrets of R-Crete Inc.. Consult Section 12 for the nature of the hazard(s).

Product not considered hazardous.

SECTION 3 - PHYSICAL DATA

Appearance: Milky liquid
Weight/Gallon: 8.78 lbs.
pH: 7-8
Boiling Point: >200° F
Solubility in water: Dilutable

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point: Non-flammable
Extinguishing Media: Non-flammable in liquid state; use water spray, foam, dry chemical. Use carbon dioxide on dried product.
Unusual fire and explosion hazard: Personnel exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
Containers exposed in a fire should be cooled with water to prevent vapor Pressure buildup leading to a rupture.

SECTION 5 - REACTIVITY DATA

Stability: Stable
Incompatibility: Not Established
Hazardous decomposition: Combustion of the dried product can yield low molecular weight hydrocarbons such as carbon monoxide and carbon dioxide.
Hazardous Polymerization: Will not occur.

