

**MATERIAL SAFETY DATA SHEET****R-CRETE HARD TOP HT-1R-CRETE INC.**

Acrylic polymer in water P.O. Box 80286

Dot Name: Acrylic polymer in water

Dot ID No.: Non regulated

Rancho Santa Margarita, CA 92688

949-888-8401 Fax 949-858-5720

**SECTION 1 - PRODUCT IDENTITY****EMERGENCY ASSISTANCE****SECTION 2 - HAZARDOUS INGREDIENTS**

<u>Ingredients</u>	<u>CAS REG. NO.</u>	<u>AMT(%)</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Ammonia	7664-41-7	-.02 %/wt.	50 ppm	25 ppm
Acrylate esters Mixture		-.05 %/wt.	Unknown	10 ppm-TWA
Benzol Alcohol	100-57-6	- 1%/wt.		

This MSDS complies with the OSHA Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not 'Hazardous' per this OSHA Standard and are considered to be trade secrets of R-Crete Inc.. Consult Section 12 for the nature of the hazard(s).

Product not considered hazardous.

**SECTION 3 - PHYSICAL DATA**

Appearance:	Milky liquid
Weight/Gallon:	8.78 lbs.
pH:	7-8
Boiling Point:	>200° F
Solubility in water:	Dilutable

**SECTION 4 - FIRE AND EXPLOSION DATA**

Flash Point:	Non-flammable
Extinguishing Media:	Non-flammable in liquid state; use water spray, foam, dry chemical. Use carbon dioxide on dried product.
Unusual fire and explosion hazard:	Personnel exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Containers exposed in a fire should be cooled with water to prevent vapor Pressure buildup leading to a rupture.

**SECTION 5 - REACTIVITY DATA**

Stability:	Stable
Incompatibility:	Not Established
Hazardous decomposition:	Combustion of the dried product can yield low molecular weight

